

The flexible comprehensive solution: BOGE C 4 (D)R to C 15 (D)R




Modular system allows customised configuration!



CONFIDENTLY CONTROLLED

The **base** control unit with LC display and pressure sensor system is included as standard. However, the **focus** control 2.0 unit is also available as an option, with its integrated efficiency indicator, well-proven BOGE leakage monitor and even an RFID input.



PERFECTLY INTEGRATED

The C series compressors are intelligently designed, with all of the essential components integrated in the compact module. The lack of hoses and connection pipes makes it practically impossible for leaks to occur. It also allows pressure losses to be minimised.



HIGHLY EFFICIENT

High air delivery rates achieved with particularly low power input – this is the trademark of the special BOGE air end of the C series compressors. The top efficiency ratings are also partly due to the intelligent arrangement of the components. All in the interest of producing consistently high-quality compressed air.



EFFECTIVELY UNITED

Where space is at a premium: the C (D)R series combines a dryer and tank on a remarkably small floor area and runs with gratifying quietness – which means it can be used directly at the workplace. Numerous treatment and filtering options make the system a flexible allrounder.

Wherever space plays a role, the BOGE C (D)R series comes into its own, because its small footprint allows it to be installed at the workplace, right where it is needed. Each of the individual elements – from the receiver to the optional refrigerant dryer and oil/water separator – come ready assembled and are delivered as a compact unit, ready for connection. In addition, the super silenced sound insulation ensures particularly quiet running. The pre-assembled pipework ensures that both the installation work and the space required are kept to an absolute minimum.

**BOGE Compressed Air Systems
GmbH & Co. KG**

Otto-Boge-Straße 1–7 · 33739 Bielefeld

Postfach 10 07 13 · 33507 Bielefeld

Tel. +49 5206 601-0 · Fax +49 5206 601-200

info@boge.de · www.boge.de

FROM THE PROFILE OF A TRUE ALL-ROUNDER

BOGE Model	Max. pressure*		Effective free air delivery**		Motor power		Dimensions*** W x D x H mm	Weight*** kg
	bar	psig	m ³ /min	cfm	kW	HP		
C 4 R	8	115	0,427	15	3,0	4,0	1880 x 927 x 1549	345
C 4 R	10	150	0,340	12	3,0	4,0	1880 x 927 x 1549	345
C 4 R	13	190	0,280	10	3,0	4,0	1880 x 927 x 1549	345
C 5 R	8	115	0,630	22	4,0	5,5	1880 x 927 x 1549	350
C 5 R	10	150	0,545	19	4,0	5,5	1880 x 927 x 1549	350
C 5 R	13	190	0,440	15	4,0	5,5	1880 x 927 x 1549	350
C 7 R	8	115	0,900	32	5,5	7,5	1880 x 927 x 1549	365
C 7 R	10	150	0,770	27	5,5	7,5	1880 x 927 x 1549	365
C 7 R	13	190	0,642	23	5,5	7,5	1880 x 927 x 1549	365
C 9 R	8	115	1,200	42	7,5	10,0	1880 x 927 x 1549	370
C 9 R	10	150	1,100	39	7,5	10,0	1880 x 927 x 1549	370
C 9 R	13	190	0,900	32	7,5	10,0	1880 x 927 x 1549	370
C 15 R	8	115	1,740	61	11,0	15,0	1815 x 830 x 1990	530
C 15 R	10	150	1,530	54	11,0	15,0	1815 x 830 x 1990	530
C 15 R	13	190	1,330	47	11,0	15,0	1815 x 830 x 1990	530
C 4 DR	8	115	0,427	15	3,0	4,0	1880 x 927 x 1549	380
C 4 DR	10	150	0,340	12	3,0	4,0	1880 x 927 x 1549	380
C 4 DR	13	190	0,280	10	3,0	4,0	1880 x 927 x 1549	380
C 5 DR	8	115	0,630	22	4,0	5,5	1880 x 927 x 1549	385
C 5 DR	10	150	0,545	19	4,0	5,5	1880 x 927 x 1549	385
C 5 DR	13	190	0,440	15	4,0	5,5	1880 x 927 x 1549	385
C 7 DR	8	115	0,900	32	5,5	7,5	1880 x 927 x 1549	400
C 7 DR	10	150	0,770	27	5,5	7,5	1880 x 927 x 1549	400
C 7 DR	13	190	0,642	23	5,5	7,5	1880 x 927 x 1549	400
C 9 DR	8	115	1,200	42	7,5	10,0	1880 x 927 x 1549	405
C 9 DR	10	150	1,100	39	7,5	10,0	1880 x 927 x 1549	405
C 9 DR	13	190	0,900	32	7,5	10,0	1880 x 927 x 1549	405
C 15 DR	8	115	1,740	61	11,0	15,0	1920 x 830 x 1990	575
C 15 DR	10	150	1,530	54	11,0	15,0	1920 x 830 x 1990	575
C 15 DR	13	190	1,330	47	11,0	15,0	1920 x 830 x 1990	575

* Max. pressure of the compressor ** Free air delivery for the complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure.

*** The specified dimensions and weights refer to the 270l receiver as standard, for the C 15 (D)R to the 350l receiver. Other receiver sizes are optionally available.

Please also take a look at our other models in the C series, all of which can be found in the C series brochure.